



RK40V

BRUSHLESS TECHNOLOGY

Cordless SDS Rotary Hammer Drill

IMPORTANT! PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE ALL SAFETY INSTRUCTIONS AND WARNINGS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO FOLLOW THESE INSTRUCTIONS MAY CAUSE DAMAGE TO PROPERTY AND/OR PERSONAL INJURY.

KEEP THESE INSTRUCTIONS SAFE AND AVAILABLE FOR FUTURE REFERENCE.

Certificate of Guarantee

This product is guaranteed for a period of 1 year, with effect from the date of purchase and applies only to the original purchaser. The guarantee can be extended a further 2 years by registering the purchase on **rikapowertools.com**. This guarantee applies to defects arising from, defective materials or faulty workmanship that become evident during the guarantee period only and does not include consumable items. The manufacturer will either repair or replace the product at their discretion, subject to the following.

That the product has been used in accordance with the guidelines as detailed in the product manual and that it has not been subject to misuse, abuse or used in a purpose for which it was not intended. That it has not been taken apart or tampered with in any way whatsoever or has been service by unauthorised persons or has been used for hire purposes.

Transit damage is excluded from this guarantee.

Claims made under this guarantee must be made to your retailer or contact us via **rikapowertools.com**, within the guarantee periods. Receipt and proof of purchase required.

The manufacturer shall not be liable for any special, exemplary, direct, indirect, incidental or consequential loss or damage under this guarantee.

Introduction

Thank you for purchasing this product which has passed through our extensive quality assurance process. Every care has been taken to ensure that it reaches you in perfect condition. However, in the unlikely event that you should experience a problem, or if we can offer any assistance or advice please do not hesitate to contact our customer service.

Safety First

Before attempting to operate this product the following basic safety precautions should always be taken to reduce the risk of fire, electric shock and personal injury. It is important to read the instruction manual to understand the application, limitations and potential hazards associated with this product.

After-Sales Service

Should you require any further assistance regarding your product or in the unlikely event of a defect occurring, please contact us at **rikapowertools.com**. When contacting us, be ready to provide the product Model No: and the serial number found on the product.

Intended Use

The tool is intended for hammer drilling and drilling in brick, concrete and stone. It is also suitable for drilling without impact in wood, metal, ceramic and plastic.

Any other application beyond the conditions established for use will be considered misuse. RIKA accepts no responsibility for improper use of this product.

Important Safety Instructions

Due to continued product refinement policy, product features and specifications can and will change without notice.

Check current features and specifications with your retailer.

The purpose of safety rules is to attract your attention to possible dangers. The safety symbols and the explanations with them, require your careful attention and understanding. The safety warnings do not by themselves eliminate any danger. The instruction or warnings they give are not substitutes for proper accident prevention measures.

SAFETY ALERT SYMBOL



Indicates danger, warning, caution or notice. May be used in conjunction with other symbols or pictures.

DANGER indicates a hazardous situation which, if not avoided, will result in death or serious injury.

WARNING indicates a hazardous situation which, if not avoided, could result in death or serious injury.

CAUTION indicates a hazardous situation which, if not avoided, could result in minor or moderate injury.

NOTICE indicates information considered important, but not hazard-related (e.g., messages relating to property damage).

Failure to obey a safety warning can result in serious injury to yourself or to others. Always follow the safety precautions to reduce the risk of fire, electric shock and personal injury.

Do not attempt to operate this tool until you have read thoroughly and completely understood the safety rules, etc. contained in this manual. Failure to comply can result

in accidents involving fire, electric shock or serious personal injury. Save this Owners Operating Manual and review it frequently for continual safe operation and for instructing others who may use this tool.

SPECIFIC SAFETY INSTRUCTIONS



WARNING! Read and understand all instructions. Failure to follow all instructions listed below could result in electrocution, fire, and/or explosion, which can cause death or serious injury.

Operations for which the power tool was not designed may create a hazard and cause personal injury.

Do not use accessories which are not specifically designed and recommended by the tool manufacturer. Just because the accessory can be attached to your power tool, it does not assure safe operation.

The product is not intended for use by children or persons with reduced physical, sensory, or mental capabilities, or lack of experience and knowledge.

Children should be adequately supervised to ensure they do not play with the product.



WARNING! Some dust particles created by power sanding, sawing, grinding, drilling and other construction jobs contain chemicals known to cause cancer, birth defects or other reproductive harm. Some examples of these chemicals are:

- Lead from lead-based paints.
- Crystalline silica from bricks and cement and other masonry products.
- Arsenic and chromium from chemically treated timber.

Important Safety Instructions



WARNING! If you suspect that paint on surfaces in your home contains lead, seek professional advice. Lead based paints should only be removed by a professional and you should not attempt to remove it yourself. Once the dust has been deposited on surfaces, hand to mouth contact can result in the ingestion of lead. Exposure to even low levels of lead can cause irreversible brain and nervous system damage. Young and unborn children are particularly vulnerable.

Do not expose to rain or water.

Wear hearing protection when necessary. Exposure to noise can cause hearing loss.



WARNING! The operation of any power tool can result in foreign objects being thrown towards your eyes, which could result in severe eye damage. Before beginning power tool operation, always wear safety goggles or safety glasses with side shield or a full face shield where needed.

Personal protective equipment suitable for the work being carried out should be worn. Personal protective equipment should include, suitable work gloves, ear protection, eye protection, respiratory protection and steel toe cap shoes or boots.

SAFETY WARNINGS SPECIFIC FOR ROTARY HAMMER DRILLS

Hold the power tool by insulated gripping surfaces, when performing an operation where the drilling accessory or fasteners may contact hidden wiring. Drilling accessories or fasteners contacting a "live" wire may make exposed metal parts of the power tool "live" and could give the operator an electric shock.

Use auxiliary handles supplied with the tool. Loss of control can cause personal injury.

Keep a firm grip on the tool at all times. Do not attempt to operate this tool without holding it with both hands. It is recommended that the auxiliary handle be used at all times. Operating this tool with one hand will result in loss of control. Breaking through or encountering hard materials such as re-bar may be hazardous as well. Tighten the side handle securely before use.

Do not operate this tool for long periods of time. Vibration caused by hammer action may be harmful to your hands and arms. Use thick cushioned gloves and limit the exposure time by taking frequent rest periods. Vibration caused by hammer-drill action may be harmful to your hands and arms.

Secure the material being drilled. Never hold it in your hand or across legs. Unstable support can cause the drill bit to bind causing loss of control and injury.

Use clamps or another practical way to secure and support the workpiece to a stable platform. Holding the work by hand or against your body leaves it unstable and may lead to loss of control.

If this machine is to be used when working at height, a suitable, stable platform or scaffold tower with hand rails and kick boards should be used.

Do not drill, fasten or break into existing walls or other blind areas where electrical wiring may exist. If this situation is unavoidable, disconnect all fuses or circuit breakers feeding this work area.

Under normal operation, the tool is designed to produce vibration. The screws can come loose easily, causing a breakdown or accident. Check tightness of screws carefully before operation.

Important Safety Instructions

Keep drill and chisel bits sharp and in good condition. This will improve cutting and reduce the load on the machine ensuring a longer life of the cutting tools and the machine.

Do not recondition bits yourself. Chisel reconditioning should be done by an authorised specialist. Improperly reconditioned chisels could cause injury.

Use only drill bits recommended by the manufacturer.

Do not attempt to modify the machine or its accessories in any way.

Do not force the machine, let the machine do the work. This will reduce the wear on the machine and bit and increase its efficiency and operating life.

When using the machine above head height wear an approved safety helmet as well as approved safety glasses or goggles and an approved face mask.

Be sure the bit is secured in place before operation.

Under normal operation, the tool is designed to produce vibration. The screws can come loose easily, causing a breakdown or accident. Check tightness of screws carefully before operation.

In cold weather or when the tool has not been used for a long time, let the tool warm up for a while by operating it under no load. This will loosen up the lubrication. Without proper warm-up, hammering operation is difficult.

Always be sure you have a firm footing. Be sure no one is below when using the tool in high locations.

Keep hands away from moving parts.

Do not leave the tool running. Never lay the tool down until the bit has come to a complete stop. Moving bits could cause injury.

Do not point the tool at any one in the area when operating. The bit could fly out and injure someone seriously.

Be aware of the high torque reaction when drilling especially when drilling masonry.

When drilling masonry do not force the drill into the work piece, let the drill and hammer action do the work.

Do not try and change any of the selector switches while the motor is running. Doing so could damage the machine.

Do not grasp the tool or place your hands too close to the spinning chuck or drill/chisel bit. Your hand may be lacerated.

Never leave the trigger in the "ON" position. Before installing the battery, check that the trigger is "OFF". Accidental start-ups can cause injury.

If the bit becomes stuck in the workpiece, release the on/off trigger immediately, reverse the direction of rotation and slowly squeeze the trigger to back out the bit. Be ready for a strong reaction torque. The drill body will tend to twist in the opposite direction as the drill bit is rotating.

When installing a drill bit, insert the shank of the bit well within the jaws of the chuck. If the bit is not inserted deep enough, the grip of the jaws over the bit is reduced and the loss of control is increased.

When removing the bit from the tool avoid contact with skin and use proper protective gloves when grasping the bit or accessory. Accessories may be hot after prolonged use.

Check to see that keys and adjusting wrenches are removed from the drill before switching the tool "ON". Keys or wrenches can fly away at high velocity striking you or a bystander.

Important Safety Instructions

Do not run the drill while carrying it at your side. A spinning drill bit could become entangled with clothing and injury may result.

Take care when carrying out demolition work using a chisel bit. Falling fragments of the demolition material could injure you or any bystanders.

Do not strike jammed bits with a hammer to dislodge them. Fragments of metal or material chips could dislodge and cause injury.

Use suitable detectors to determine if utility lines are hidden in the work area or call the local utility company for assistance. Contact with electric lines can lead to fire and electric shock. Damaging a gas line can lead to explosion. Penetrating a water line causes property damage or may cause an electric shock.

SAFETY WARNINGS WHEN USING LONG DRILL BITS

Never operate at higher speed than the maximum speed rating of the drill bit. At higher speeds, the bit is likely to bend if allowed to rotate freely without contacting the workpiece, resulting in personal injury.

Always start drilling at low speed and with the bit tip in contact with the workpiece. At higher speeds, the bit is likely to bend if allowed to rotate freely without contacting the workpiece, resulting in personal injury.

Apply pressure only in direct line with the bit and do not apply excessive pressure. Bits can bend causing breakage or loss of control, resulting in personal injury.

ADDITIONAL SAFETY INSTRUCTIONS FOR BATTERIES

Only use the following batteries and chargers with this tool.

RIKA 2000mAh Li-Ion Battery: RK40B2
RIKA 4000mAh Li-Ion Battery: RK40B4
RIKA 4000mAh Li-Ion Battery: RK40TB4

RIKA 2.4A Fast Charger: RK40FC2
RIKA 4.0A Fast Charger: RK40FC4
RIKA 4.5A Dual Fast Charger: RK40DFC4

Battery packs are shipped in a low charge condition. You should charge a battery pack fully before use.

Do not incinerate a battery pack even if it is seriously damaged or can no longer hold a charge. A battery pack can explode in a fire.

A small leakage of liquid from the battery pack may occur under extreme usage or temperature conditions. This does not necessarily indicate a failure of the battery pack. However, if the outer seal is broken and this leakage comes into contact with your skin wash the affected area quickly with soap and water. If the leakage gets in your eyes flush your eyes with clean water for a minimum of 10 minutes and seek immediate medical attention.

Never attempt to open a battery pack for any reason. If the plastic housing a battery pack breaks open or cracks, immediately discontinue its use and do not recharge it.

Do not store or carry a spare battery pack in a pocket or toolbox or any other place where it may come into contact with metal objects. The battery pack may be short-circuited causing damage to the battery pack, burns or a fire.

CHARGING BATTERIES

When charging a new battery pack it should be fully discharged followed by a full charge for the charging rate for the battery as stated in its product manual plus 30 minutes. This should then be followed by a full discharge and a further full charge for the charging rate for the battery as stated in its product manual plus 30 minutes. This procedure will condition the battery and equalise the cell voltages. Following this procedure will ensure the optimum operation of the battery.

Important Safety Instructions

When repeatedly using a charger to charge a number of batteries always allow the charger to cool down before charging another battery.

It is recommended that the cooling down period is not less than 30 to 45 minutes.

When charging a battery that has been discharged during heavy use allow the battery to cool down before charging. It is recommended that the cooling down period is not less than 30 to 45 minutes.

Battery packs need to be recharged with a reasonable amount of care, largely because they can be damaged by overcharging.

Overcharging can result in the battery temperature and internal pressure to rise rapidly. This can cause the cells to distort and lose electrolyte, and in extreme cases where the internal pressure is extremely high they can even explode.

This situation can also arise when an overcharged battery is fitted to the product and is being used. In order to avoid this extreme situation it is of vital importance that NiCad and/or Li-Ion batteries are fully discharged before charging and that the charge time is not exceeded except when "Conditioning" a new battery. Repeated charging of partially discharged batteries could cause failure of one or more of the cells.

SELF DISCHARGE

A lithium battery can self discharge and lose its stored charge. Typically it can lose approximately 5% of its charge in the first month after fully charging (when stored at room temperature), and then loses it by a further 3% per month. When stored at higher temperatures the self discharge rate will be accelerated.

BATTERY CHARGING INDOORS

Chargers are designed to be used indoors. We do not recommend that chargers are used inside your home. Ideally batteries

should be charged on a bench in a workshop, garage or shed. If the charging operation is to be carried out in your home the area must be well ventilated and the charger must be placed on a non combustible surface ensuring that the ventilation slots are not blocked.

Never exceed the charging time except when "Conditioning" a new battery, as this could damage a battery and charger.

BATTERY DISPOSAL

When a battery fails to charge or maintain its charge, its usable life is exhausted. To preserve natural resources, please recycle or dispose of a battery pack properly. Before disposal ensure that the battery pack is fully discharged by operating your cordless product, then remove the battery pack from the tool housing and cover the battery pack connections with heavy duty tape, to prevent short circuit and energy discharge which could result in a fire. Do not attempt to open or remove any of the components.

Consult your local waste authority for information regarding available recycling and / or disposal options.

SPECIFIC SAFETY INSTRUCTIONS

RE-CHARGEABLE BATTERIES

Batteries may leak or explode if not charged or handled correctly. Always observe the following precautions when handling batteries. Ensure that the machine is switched off before removing or fitting batteries.

Do not use a battery with any other product that is not recommended.

Do not attempt to fit a battery the wrong way round.

Do not short out, or attempt to dismantle a battery.

Do not expose a battery to flames or excessive heat.

Important Safety Instructions

Do not immerse in or expose a battery to water.

Do not store or transport a battery with loose metal objects such drill and driver bits.

Batteries are prone to leakage when discharged. To avoid damage to the product, remove or re-charge the battery when no charge remains. Store the battery in a cool place when not in use.

After prolonged use a battery may become hot. Before removing a battery, switch the machine off and allow the battery to cool down. Do not use the battery if you notice any discolouration or distortion of the battery casing.

RESIDUAL RISKS

Even when the unit is used as prescribed it is not possible to eliminate all residual risk factors. The following hazards may arise in connection with the unit's construction and design:

1. Damage to hearing caused by noise. Wear suitable hearing protection and limit exposure.
2. Injury to the eyes. Wear protective eye shields or goggles when using the product.
3. Injury caused by vibration. Limit exposure. Follow the instructions in Risk Reduction.
4. Electric shock caused by contact with hidden wires. Hold the product only by insulated services.
5. Injury caused by dust. Dust created by operating the product can cause respiratory injury. Wear appropriate dust control mask with filters suitable for protecting against particles from the material being worked on.

RISK REDUCTION

It has been reported that vibrations from handheld tools may contribute to a condition called Raynaud's Syndrome in certain individuals.

Symptoms may include tingling, numbness, and blanching of the fingers, usually apparent upon exposure to cold.

Hereditary factors, exposure to cold and dampness, diet, smoking and work practices are all thought to contribute to the development of these symptoms. There are measures that can be taken by the operator to possibly reduce the effects of vibration:

Keep your body warm in cold weather. When operating the unit, wear gloves to keep the hands and wrists warm.

It is reported that cold weather is a major factor contributing to Raynaud's Syndrome.

After each period of operation, exercise to increase blood circulation.

Take frequent work breaks. Limit the amount of exposure per day.

If you experience any of the symptoms of this condition, immediately discontinue use and see your doctor about these symptoms.



WARNING! Injuries may be caused, or aggravated, by prolonged use of a tool. When using any tool for prolonged periods, ensure you take regular breaks.

WARNING

This unit produces an electromagnetic field during operation. This field may under some circumstances interfere with active or passive medical implants. To reduce the risk of serious or fatal injury, we recommend persons with medical implants to consult their physician and the medical implant manufacturer before operating this unit.

Important Safety Instructions

GENERAL SAFETY RULES



WARNING! Read all instructions. Failure to follow all instructions listed below may result in electric shock, fire and/or serious injury. The term "power tool" in all of the warnings listed below refers to your mains operated (corded) power tool or battery operated (cordless) power tool.

SAVE THESE INSTRUCTIONS

1) WORK AREA

- a) **Keep work area clean and well lit.** Cluttered and dark areas invite accidents.
- b) **Do not operate power tools in explosive atmospheres, such as in the presence of flammable liquids, gases or dust.** Power tools create sparks which may ignite the dust or fumes.
- c) **Keep children and bystanders away while operating a power tool.** Distractions can cause you to lose control.

2) ELECTRICAL SAFETY

- a) **Power tool plugs must match the outlet. Never modify the plug in any way. Do not use any adapter plugs with earthed (grounded) power tools.** Unmodified plugs and matching outlets will reduce risk of electric shock.
- b) **Avoid body contact with earthed or grounded surfaces such as pipes, radiators, ranges and refrigerators.** There is an increased risk of electric shock if your body is earthed or grounded.
- c) **Do not expose power tools to rain or wet conditions.** Water entering a power tool will increase the risk of electric shock.
- d) **Do not abuse the cord. Never use the cord for carrying, pulling or unplugging the power tool. Keep cord away from heat, oil, sharp edges or moving parts.** Damaged or entangled cords increase the risk of electric shock.
- e) **When operating a power tool outdoors, use an extension cord suitable for outdoor use.** Use of a cord suitable for outdoor use reduces the risk of electric shock.
- f) **If operating a power tool in a damp location is unavoidable, use a residual current device (RCD) protected supply.** Use of an RCD reduces the risk of electrical shock.
NOTE: The term "residual current device (RCD)" can be replaced by the term "ground fault circuit interrupter (GFCI)" or "earth leakage circuit breaker (ELCB)".

3) PERSONAL SAFETY

- a) **Stay alert, watch what you are doing and use common sense when operating a power tool. Do not use a power tool while you are tired or under the influence of drugs, alcohol or medication.** A moment of inattention while operating power tools may result in serious personal injury.
- b) **Use personal protective equipment. Always wear eye protection.** Safety equipment such as dust mask, non-skid safety shoes, hard hat, or hearing protection used for appropriate conditions will reduce personal injuries.
- c) **Prevent unintentional starting. Ensure the switch is in the off-position before connecting to power source and/or battery pack, picking up or carrying the tool.** Carrying power tools with your finger on the switch or energising power tools that have the switch on invites accidents.

Important Safety Instructions

- d) **Remove any adjusting key or wrench before turning the power tool on.** A wrench or a key left attached to a rotating part of the power tool may result in personal injury.
 - e) **Do not overreach. Keep proper footing and balance at all times.** This enables better control of the power tool in unexpected situations.
 - f) **Dress properly. Do not wear loose clothing or jewellery. Keep your hair, clothing and gloves away from moving parts.** Loose clothes, jewellery or long hair can be caught in moving parts.
 - g) **If devices are provided for the connection of dust extraction and collection facilities, ensure these are connected and properly used.** Use of these devices can reduce dust related hazards.
 - h) **Do not let familiarity gained from frequent use of tools allow you to become complacent and ignore tool safety principles.** A careless action can cause severe injury within a fraction of a second.
- ## 4) POWER TOOL USE AND CARE
- a) **Do not force the power tool. Use the correct power tool for your application.** The correct power tool will do the job better and safer at the rate for which it was designed.
 - b) **Do not use the power tool if the switch does not turn it on and off.** Any power tool that cannot be controlled with the switch is dangerous and must be repaired.
 - c) **Disconnect the plug from the power source and/or the battery pack from the power tool before making any adjustments, changing accessories, or storing power tools.** Such preventive safety measures reduce the risk of starting the power tool accidentally.
 - d) **Store idle power tools out of the reach of children and do not allow persons unfamiliar with the power tool or these instructions to operate the power tool.** Power tools are dangerous in the hands of untrained users.
 - e) **Maintain power tools. Check for misalignment or binding of moving parts, breakage of parts and any other condition that may affect the power tools operation. If damaged, have the power tool repaired before use.** Many accidents are caused by poorly maintained power tools.
 - f) **Keep cutting tools sharp and clean.** Properly maintained cutting tools with sharp cutting edges are less likely to bind and are easier to control.
 - g) **Use the power tool, accessories and tool bits etc., in accordance with these instructions and in the manner intended for the particular type of power tool, taking into account the working conditions and the work to be performed.** Use of the power tool for operations different from intended could result in a hazardous situation.
 - h) **Keep handles and grasping surfaces dry, clean and free from oil and grease.** Slippery handles and grasping surfaces do not allow for safe handling and control of the tool in unexpected situations.
 - g) **When using the tool, do not wear cloth work gloves which may be entangled.** The entanglement of cloth work gloves in the moving parts may result in personal injury.
- ## 5) BATTERY TOOL USE AND CARE
- a) **Recharge only with the charger specified by the manufacturer.** A charger that is suitable for one type of battery pack may create a risk of fire when used with another battery pack.

Important Safety Instructions

- b) **Use power tools only with specifically designated battery packs.** Use of any other battery packs may create a risk of injury and fire.
- c) **When battery pack is not in use, keep it away from other metal objects, like paper clips, coins, keys, nails, screws or other small metal objects, that can make a connection from one terminal to another.** Shorting the battery terminals together may cause burns or a fire.
- d) **Under abusive conditions, liquid may be ejected from the battery; avoid contact. If contact accidentally occurs, flush with water. If liquid contacts eyes, additionally seek medical help.** Liquid ejected from the battery may cause irritation or burns.

6) SERVICE

- a) **Have your power tool serviced by a qualified repair person using only identical replacement parts.** This will ensure that the safety of the power tool is maintained.
- b) **Never service damaged battery packs.** Service of battery packs should only be performed by the manufacturer or authorised service providers.
- c) **Follow instruction for lubricating and changing accessories.**

Technical Specification

Rated Voltage:	40V DC
Motor:	Brushless
No Load Speed:	0-980/min
Impact Rate:	0-4500bpm
Impact Energy:	2.4J
Drilling Capacity (Wood):	28mm
Drilling Capacity (Steel)	13mm
Drilling Capacity (Masonry):	26mm
Bit Holder:	SDS plus
Spindle Collar Diameter:	10mm
Weight:	2.92kg

Sound Pressure Level:	L_{PA} 91.9 dB(A), $K=3dB(A)$
Sound Power Level:	L_{WA} 99.9 dB(A), $K=3dB(A)$
Vibration Levels	
(Hammer Drill Mode):	$12.293m/s^2$, $K=1.5m/s^2$
(Hammer Drill & Chisel Mode):	$20.892m/s^2$, $K=1.5m/s^2$
(Chisel Mode):	$18.937m/s^2$, $K=1.5m/s^2$

Safety Symbols

Some of the following symbols may be used on this product. Please study them and learn their meaning. Proper interpretation of these symbols will allow you to operate the product better and safer.	
SYMBOL	DESIGNATION/EXPLANATION
	Indicates danger, warning or caution. It means attention!!! Your safety is involved.
	Your manual contains special messages to bring attention to potential safety concerns as well as operating and servicing information. Please read all the information carefully to ensure satisfaction and safe use.
	Wear eye, hearing and head protection when operating this equipment.
	Do not expose to rain or use in damp locations.
	Waste electrical products should not be disposed of with household waste. Please recycle where facilities exist. Check with your Local Authority or retailer for recycling advice.
	Conforms to relevant safety standards.

Unpacking



CAUTION. This packaging contains sharp objects. Take care when unpacking. Remove the machine, together with the accessories supplied, from the packaging. Check carefully to ensure that the machine is in good condition and account for all the accessories listed in this manual. Also make sure that all the accessories are complete.

If any parts are found to be missing, the machine and its accessories should be returned together in their original packaging to the retailer. Do not throw the packaging away, keep it safe throughout the guarantee period, then recycle if possible, otherwise dispose of it by the proper means. Do not let children play with empty plastic bags due to the risk of suffocation.

Components & Controls



- | | |
|----------------------------------|--------------------------------------|
| 01. SDS-plus tool holder | 08. On/Off trigger |
| 02. Dust protection cap | 09. Soft-grip handle |
| 03. Locking sleeve | 10. Function mode selector dial |
| 04. Depth stop | 11. Battery mount |
| 05. Function mode release button | 12. LED worklight |
| 06. Vibration damping | 13. Auxiliary handle |
| 07. Forward/lock/reverse button | 14. Button for depth stop adjustment |

Assembly & Adjustments



WARNING! Do not use this product if it is not completely assembled or if any parts appear to be missing or damaged. Use of a product that is not properly and completely assembled or with damaged or missing parts could result in serious personal injury.



WARNING! Do not attempt to modify this product or create accessories or attachments not recommended for use with this product. Any such alteration or modification is misuse and could result in a hazardous condition leading to possible serious personal injury.



WARNING! To reduce the risk of injury, turn unit off and disconnect the battery pack from the machine before installing and removing accessories, before adjusting or changing setups or when making repairs. Be sure the forward/reverse switch is in the lock-off (centre) position. An accidental start-up can cause injury.

AUXILIARY HANDLE



WARNING. To reduce the risk of personal injury, ALWAYS operate the tool with the auxiliary handle properly installed. Failure to do so may result in the auxiliary handle slipping during tool operation and subsequent loss of control. Hold tool with both hands to maximise control.



CAUTION. After adjusting the auxiliary handle, make sure that the auxiliary handle is firmly secured. Otherwise you could lose control of the power tool when working.

ADJUSTING THE AUXILIARY HANDLE

You can rotate the auxiliary handle to any angle for a safe work posture that minimises fatigue.

Turn the lower gripping end of the auxiliary handle anti-clockwise and rotate the auxiliary handle into the required position. Turn the lower gripping end of the auxiliary handle clockwise to retighten it, Fig.1.




Fig.1

INSTALLING SDS-PLUS BITS (NOT SUPPLIED)




WARNING! Wear protective gloves when changing SDS plus bits. The SDS-plus tool holder may heat up significantly when it is used for long periods.



CAUTION. The dust protection cap largely prevents the penetration of drilling dust into the SDS-plus tool holder during operation. When inserting the SDS-plus bit, make sure that the dust protection cap does not become damaged.

The SDS-plus drill holder enables you to change the SDS-plus bits easily without needing to use additional tools.

Assembly & Adjustments



Before inserting the SDS-plus bit into the SDS-plus tool holder clean and lightly grease the insertion end of the SDS-plus bit.

Insert the SDS-plus bit into the SDS-plus tool holder. Turn the drill bit and push it in until it locks automatically, Fig.2.


After installing the SDS-plus bit, always make sure that the SDS-plus bit is securely held in place by trying to pull it out.

As a requirement of the system, the SDS-plus bit can move freely. This causes a certain radial run-out at no-load, which has no effect on the accuracy of the drill hole, as the drill bit centres itself upon drilling.

REMOVING SDS-PLUS BITS

Pull the locking sleeve back and remove the SDS-plus bit, Fig.3.

Always wear protective gloves when removing SDS plus bits, They may be hot.



Assembly & Adjustments

USING A KEYED CHUCK (NOT SUPPLIED)



WARNING! Do not use a keyed drill chuck for hammer drilling or chiselling applications! It is intended exclusively for drilling with drill bits for wood and metal.

NOTE: A keyed drill chuck allows normal bits (non SDS type) to be used with the machine.

To use a keyed chuck with this machine you will need a SDS-plus adaptor (not supplied).

Clean and lightly grease the insertion end of the shank.

To fit a keyed drill chuck adaptor, grip and pull back the locking sleeve and insert the SDS adaptor of the keyed chuck until it locks automatically.

Insert the chuck key (not supplied) into one of the holes on the keyed drill chuck and then turn the key anticlockwise until the tool socket is opened wide enough to insert the drill bit.

Insert the drill bit all the way to the stop.

Insert the chuck key into one of the holes on the keyed drill chuck and then turn the chuck key clockwise until the drill bit is securely fastened and centred in the keyed drill chuck.



WARNING! After short operation, switch the machine off, disconnect the battery pack and check once again that the drill bit is properly fastened. Caution, the drill bit could be hot.

INSTALLING THE DEPTH STOP

The depth gauge is convenient for drilling holes of uniform depth.

To install the depth stop press and hold the depth stop adjustment button and then insert the depth stop into the hole, Fig.4.

Adjust the depth stop by moving it back and forth while pressing the depth stop adjustment button. After the adjustment, release the depth stop adjustment button to lock the depth stop.




Fig.4

Assembly & Adjustments

INSTALLING A RIKA BATTERY PACK



WARNING! Always remove battery pack from your tool when you are assembling parts, making adjustments, cleaning, carrying, transporting or when not in use. Removing battery pack will prevent accidental starting that could cause serious personal injury.

Slide the battery pack into the battery mount, Fig.5.



Fig.5

NOTE: The battery has raised ribs which allows it to fit into the tool only one way. Make sure the battery pack snaps into place and that battery pack is secured in the tool before beginning operation. Improper installation of the battery pack can cause damage to internal components.

REMOVING THE BATTERY PACK

Locate the battery release catch on the top of the battery and press downwards, Fig.6. Whilst holding down the battery release catch slide the battery pack away from the tool.




Fig.6

Operation



WARNING! To reduce the risk of serious personal injury, disconnect the battery pack from the tool before making any adjustments or removing/installing attachments or accessories.



CAUTION. When using the tool in high places, make sure that no one is below you. Dropping your tool from a height may cause serious injuries.



CAUTION. If the tool malfunctions or makes abnormal noises, stop using the tool. then contact your local RIKA Service Centre.

IMPORTANT. Verify the following every time the rotary hammer drill is used:

1. Safety glasses, safety goggles, or face shield is being worn.
2. Hearing protection is being worn.

Operation


3. The auxiliary handle is installed. Firmly hold the tool by both auxiliary handle and rear handle during operations.
4. The bit is in good condition and is properly tightened onto the tool holder.

TURNING THE ROTARY HAMMER DRILL ON/OFF



CAUTION. Before installing the battery pack into the tool, always check to see that the On/Off trigger actuates properly and returns to the "OFF" position when released.

To start the machine squeeze the On/Off trigger, Fig. 7. Light pressure on the On/Off trigger results in low speed, allowing drilling to begin in a smooth, controlled manner.



NOTE: You may hear a high pitched noise from the switch during use. Do not be concerned; this is a normal part of the switch function.

To turn the tool off, release the On/Off trigger. Your tool is equipped with a brake. The chuck will stop when the On/Off trigger is fully released.

LED WORKLIGHT



CAUTION. Do not directly look into the source of light.

Pull the On/Off trigger to activate the LED worklight. The LED worklight will illuminate continuously while the On/Off trigger is being pulled. The LED worklight goes out 10 seconds after releasing the trigger.

NOTE: The worklight is for lighting the immediate work surface and is not intended to be used as a flashlight.

FORWARD AND REVERSE SWITCH

A forward/reverse switch determines the direction of the tool and also serves as a lock-off function.

This feature is selected via a slide switch located above the On/Off trigger, Fig.8.



To select direction of the rotary hammer drill rotation simply push the switch fully in on the left side for reverse rotation. To change to forward rotation push the switch fully in on the right side of the handle.

NOTE: As a safety precaution from accidental engagement while being carried pushing the forward/reverse switch into the middle or lock-off position will render the tool inoperative.

Operation



CAUTION. To prevent gear damage, always allow the tool to come to a complete stop before changing the direction of rotation or selecting the lock-off function.

NOTE: The rotary hammer drill will not run unless the forward/lock/reverse switch is pushed fully to the left or right.

Avoid running the drill at low speeds for extended periods of time. Running at low speeds under constant usage may cause the rotary hammer drill to become overheated. If this occurs, cool the drill by running it without a load and at full speed.



CAUTION. Always check the direction of rotation before operation.

FUNCTION MODE SELECTOR




CAUTION. Do not rotate the function mode selector dial when the tool is running. The tool will be damaged.




CAUTION. To avoid rapid wear on the function mode selector mechanism, be sure that the function mode selector dial is always positively located in one of the function mode positions.

The function mode of the rotary hammer drill is selected using the function mode selector dial.


To change the function mode, press the function mode release button and turn the function mode selector dial until it clicks into the required position.



Position for hammer drilling into concrete or stone.




Position for drilling without impact in wood, metal, ceramic and plastic and for screwdriving. Use with keyed chuck adaptor (not supplied).



Variable-Lock position for adjusting the chisel position

The function mode release button will not engage in this position.



Position for chiselling.

INSTRUCTIONS FOR USE



WARNING! Always observe the safety instructions and applicable regulations.



CAUTION. Always insert the battery cartridge all the way until it locks in place. Incorrect installation may result in the battery falling out of the tool, causing injury to you or someone around you.

PROPER HAND POSITION



WARNING! To reduce the risk of serious personal injury, ALWAYS hold securely in anticipation of a sudden reaction.



WARNING! To reduce the risk of serious personal injury, ALWAYS use proper hand position as shown in Fig.9. Proper hand position requires one hand on the soft grip handle and one hand on the auxiliary handle.

Operation



OPERATION



CAUTION! Always make sure that the workpiece is secured before operation.



CAUTION! Do not pull the tool out forcibly even the bit gets stuck. Loss of control may cause injury.

NOTE: If the battery cartridge is in low temperature, the tool's capability may not be fully obtained. In this case, warm up the battery cartridge by using the tool with no load for a while to fully obtain the tool's capability.

Check the product, its battery pack as well as accessories for damage before each use. Do not use the product if it is damaged or shows wear.

Double check that accessories or drill bits are properly fixed.

Always use the auxiliary handle and firmly hold the tool by both auxiliary handle and rear handle during operations. Failure to do so may result in the loss of control of the tool and potentially severe injury.

Ensure that the air vents are always unobstructed and clean. Clean them if necessary with a soft brush. Blocked air vents may lead to overheating and damage the product.


Switch the product off immediately if you are disturbed while working by other people entering the working area. Always let the product come to complete stop before putting it down.

Do not overwork yourself. Take regular breaks to ensure you can concentrate on the work and have full control over the product.



WARNING! Keep in mind that there are buried objects hidden in every household. Ensure that there are no gas, water or power lines hidden in the working area that may be hit before operation - danger of electrical shock and serious damage to people and property. Use a suitable detector to trace such objects in advance!

HAMMER DRILLING OPERATION



Set the function mode selector dial to the hammer drilling symbol.

Insert the appropriate drill bit. For best results use high quality carbide-tipped bits.

Adjust the auxiliary handle as required.

Mark the spot where the hole is to be drilled. When drilling hard, smooth surfaces, use a centre punch to mark the desired hole location. This will prevent the drill bit from slipping off-centre as the hole is started.

Place the drill bit on the spot and depress the On/Off trigger to start the drill.

Move the drill bit into the workpiece, applying only enough pressure to keep the bit cutting. Do not force the drill or apply side pressure to elongate a hole. Let the tool do the work.

Operation




WARNING! Be prepared for binding at bit breakthrough. When these situations occur, drill has a tendency to grab and kick opposite to the direction of rotation and could cause loss of control when breaking through material. If not prepared, this loss of control can result in possible serious injury.

If the bit jams in the workpiece or if the drill stalls, stop the tool immediately. Remove the bit from the workpiece and determine the reason for jamming.

NOTE: This drill has an electric brake. When the On/Off trigger is released, the chuck stops turning. When the brake is functioning properly, sparks will be visible through the vent slots on the housing. This is normal and is the action of the brake.

DRILLING OPERATION



Set the function mode selector dial to the drilling symbol.

Fit a keyed chuck with SDS-plus adaptor (not supplied).

Open the keyed chuck by turning it with a chuck key (not supplied). Insert a appropriate drill bit for the material being drilled.

Clamp the drill bit evenly in the keyed chuck with the chuck key.

Adjust the auxiliary handle as required.

Secure the material to be drilled in a vice or with clamps to keep it from turning as the drill bit rotates.

Mark the spot where the hole is to be drilled.

Place the drill bit on the spot and depress the On/Off trigger to start the drill.

FOR WOOD:

Begin drilling at a very low speed to prevent the bit from slipping off the starting point. Increase the speed as the drill bit bites into the material.

When drilling through holes, place a block of wood behind the workpiece to prevent ragged or splintered edges on the back side of the hole.

NOTE: Pressing excessively on the tool will not speed up the drilling. In fact, this excessive pressure will only serve to damage the tip of your drill bit, decrease the tool performance and shorten the service life of the tool.

FOR METAL:

When drilling metals, use a light oil on the drill bit to keep it from overheating. The oil will prolong the life of the bit and increase the drilling action.


Begin drilling at a very low speed to prevent the bit from slipping off the starting point.

Maintain a speed and pressure which allows cutting without overheating the bit. Applying too much pressure will:

- Overheat the drill;
- Wear the bearings;
- Bend or burn bits; and
- Produce off-centre or irregular-shaped holes.

When drilling large holes in metal, start with a small bit, then finish with a larger bit. Also, lubricate the bit with oil to improve drilling action and increase bit life.

CHISELLING OPERATION



Set the function mode selector dial to the chiselling symbol.

Insert the appropriate chisel bit.

Operation

Check the chisel bit is securely locked in place.

Adjust the auxiliary handle as required.

Depress the On/Off trigger to start the drill.

Let the tool do the work. Do not lean your full weight into the drill. Apply just enough steady pressure to keep the bit in contact with the material.

Find fracture points. Start at the edges or corners rather than the centre of a large

slab. For hard concrete, drilling pilot holes first can create fault lines to make chiselling easier.

Hold the tool firmly with both hands using the auxiliary handle for leverage.

Always wear eye protection, gloves, hearing protection, and a dust mask (especially when working with silica-heavy materials like mortar or brick).

Maintenance



WARNING! Always be sure that the tool is switched off and the battery pack is removed before attempting to perform inspection or maintenance.

This power tool normally requires no maintenance; from time to time the ventilation slots on the motor casing should be cleaned out. If the unit should become defective, repair should be performed by an authorised service agent for electric tools.

The tool may be cleaned most effectively with compressed dry air. Always wear safety goggles when cleaning tools with compressed air.

Ventilation openings and switch levers must be kept clean and free of foreign matter. Do not attempt to clean by inserting pointed objects through openings.

Avoid using solvents when cleaning plastic parts. Most plastics are susceptible to damage from various types of commercial solvents and may be damaged by their use. Use clean cloths to remove dirt, dust, oil, grease, etc.



WARNING! Do not at any time let brake fluids, gasoline, petroleum based products, penetrating oils, etc., come in contact with plastic parts. Chemicals can damage, weaken or destroy plastic which may result in serious personal injury.

Electric tools used on fibreglass material, wallboard, spackling compounds or plaster are subject to accelerated wear and possible premature failure because the fibreglass chips and grindings are highly abrasive to bearings, brushes, commutators, etc. Consequently, we do not recommend using this tool for extended work on these types of materials. However, if you do work with any of these materials, it is extremely important to clean the tool using compressed air.

Always store your power tool in a dry place.

Occasionally you may see sparks through the ventilation slots. This is normal and will not damage your power tool.

Maintenance



WARNING! Always wear safety goggles or safety glasses with side shields during power tool operation or when blowing dust. If operation is dusty, also wear a dust mask.

LUBRICATION

All of the bearings in this tool are lubricated with a sufficient amount of high grade lubricant for the life of the unit under normal operating conditions. Therefore, no further lubrication is required.

Service

Now that you have purchased your tool, should a need ever exist of repair or service, simply contact your nearest RIKA Authorised Service Centre or other qualified service organisation. Be sure to provide all pertinent facts when you call or visit.

Environmental Protection

Information for (private householders) for the environmentally responsible disposal of Waste Electrical and Electronic Equipment (WEEE)



This symbol on products and or accompanying documents indicates that used and end of life electrical and electronic equipment should not be disposed of in household waste. For the proper disposal, treatment, recovery and recycling, please take these products to designated collection points, where they will be accepted on a free of charge basis. Alternatively, in some countries you may be able to return your products to your retailer upon the purchase of an equivalent new product. Disposing of this product correctly will help to save valuable resources and prevent any potential adverse effects on human health and the environment which could otherwise arise from inappropriate waste disposal and handling. Please contact your local authority

for further details of your nearest designated collection point. Penalties may be applicable for incorrect disposal of this waste in accordance with national legislation.

FOR BUSINESS USERS IN THE EUROPEAN UNION.

If you wish to discard electrical and electronic equipment, please contact your dealer or supplier for further information.

Information on Disposal in other Countries outside the European Union.

This Symbol is only valid in the European Union.

If you wish to dispose of this product, please contact your local authorities or dealer and ask for the correct method of disposal.

EC Declaration of Conformity

1. **Product model:** RK40HA16
2. **Name and address of the manufacturer or his authorised representative:**

RIKA

SGS Engineering (UK) Ltd
Unit 1 West Side Park, Raynesway,
Derby, DE21 7AZ

3. **This declaration of conformity is issued under the sole responsibility of the manufacturer.**
4. **Object of the declaration:**
- Equipment:** 40V Cordless SDS Rotary Hammer Drill
Brand name: RIKA
Model/type: RK40HA16
5. **The object of the declaration described above is in conformity with the relevant statutory requirements:**

Supply of Machinery (Safety) Regulations 2008
Electrical Equipment (Safety) Regulations 2016
Electromagnetic Compatibility Regulations 2016
The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012

6. **References to the relevant designated standards used or references to the other technical specifications in relation to which conformity is declared:**

BS EN55014-1	BS EN62841-1
BS EN55014-2	BS EN62841-2-6

7. **The person authorised to compile the technical file:**

Name: Neil Sansom
Address: SGS Engineering (UK) Ltd, Unit 1 West Side Park,
Raynesway, Derby, DE21 7AZ

Signed for and on behalf of:

Authorised Representative



Neil Sansom, CEO
Date: 06/03/2026

**UK
CA 26**